



Gazpromneft GL-4 90 and 140

Monograde Automotive Gear Oils



Mechanical transmissions



Good EP properties



Mineral

Gazpromneft GL-4 oils are high performance, multipurpose, mild extreme pressure lubricants designed for applications where API GL-4 performance is required. They are blended from highly refined mineral base oils and combined with extreme pressure additives plus rust, oxidation, and foam inhibitors to extend the life of gear components. Gazpromneft GL-4 oils prolong gear set's life and increasing its efficiency.

Applications



- Heavy duty manual transmissions, axles and final drives requiring API GL-4 level performance
- Passenger cars, on-highway light and heavy duty trucks, and commercial vehicles
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Other heavy duty industrial and automotive applications including hypoid gears operating under moderate to severe conditions
- Not recommended for use in automotive and heavy duty differentials using offset spiral bevel (hypoid) gear sets where API GL-5 gear oils are specified

Features	Advantages and Potential Benefits		
Good thermal and oxidation stability	Reduced deposits and sludge build-up for extended gear and bearing life		
Good rust and corrosion protection	Effective prevention of corrosion caused by water and acid produced through deterioration process		
Low foaming	Prevention of foaming for smoother lubrication		
Compatible with all common seal materials	Excellent leakages control		

Meet the requirements:

• API GL-4

Typical Characteristics

Properties	Method	Gazpromneft GL-4 90	Gazpromneft GL-4 140
SAE Viscosity Grade	SAE J306	90	140
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	16,7	25,7
Flash Point (COC), °C	ASTM D92	238	254
Pour Point, °C	ASTM D97	-15	-15
Density @15°C, kg/m ³	ASTM D4052	897	903
Tribological characteristics, Four-Ball Method			
Load-wear index, N	ASTM D2783	570	585
Weld point, N		3950	4350

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.qazpromneft-oil.com While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>OilSupport@gazprom-neft.ru</u> 05/2018

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

ISO 9001

© ISO 14001

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com

ISO/TS 16949

OHSAS 18001

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>OilSupport@gazprom-neft.ru</u> 05/2018