



Gazpromneft Premium L 20W-50

Passenger Vehicle Engine Oils



Engine oil



Minerals



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 20W-50 is high quality mineral engine oils providing high level of protection and performance. It is formulated with improved additive package providing wear, corrosion and rust protection to ensure optimum engine operation. It delivers long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with ACEA A3/B3 or API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

| Features | Advantages and Potential Benefits |
|--|--|
| Multi-purpose application | High quality formulation suitable for a wide range of vehicles requiring premium quality product |
| Wear protection | Strong oil film provides protection against wear under all operating conditions for long engine life |
| Improved thermal and oxidation stability | Helps to resist oil aging allowing extended drain interval protection |
| Deposit control | Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness |
| Stay-in-grade | Keeps protective oil film during the whole drain interval and maintains viscosity grade |

Meets the requirements

- ACEA A3/B3
- API SL
- API CF
- AVTOVAZ

Typical Characteristics

| Properties | Method | Gazpromneft Premium L 20W-50 |
|--|------------|------------------------------|
| SAE Viscosity Grade | SAE J300 | 20W-50 |
| Kinematic Viscosity @40°C, mm ² /s | ASTM D445 | 178,2 |
| Kinematic Viscosity @100°C, mm ² /s | ASTM D445 | 18,9 |
| Viscosity Index | ASTM D2270 | 120 |
| Flash Point (COC), °C | ASTM D92 | 252 |
| Pour Point, °C | ASTM D97 | -29 |
| Total Base Number, mg KOH/g | ISO 6619 | 9,0 |
| Density @15°C, kg/m ³ | ASTM D4052 | 893 |
| Sulfated Ash, wt% | ASTM D874 | 1,3 |

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.